

PROFILY UZAVŘENÉ (JÄKLY) – ČTVERCOVÉ

Normy technicko dodacích podmínek	DIN 59411
Materiál	W.Nr.1.4301
Výrobní délky	6 m
Povrch	mořený, kartáčovaný, broušený

Dle požadavku dodáme jÄkly dalších rozměrů a jakostí.

Rozměr mm	Tloušťka stěny mm • Hmotnost kg/m							
	1	1,2	1,5	2	2,5	3	3,5	4
15 x 15	0,453	0,539	0,661					
19,05 x 19,05	0,592	0,711	0,888					
20 x 20	0,610	0,724	0,890	1,159				
22,2 x 22,2	0,671	0,810	1,013	1,350				
25 x 25	0,771	0,917	1,129	1,475				
25,4 x 25,4	0,781	0,955	1,209	1,587				
30 x 30	0,931	1,108	1,371	1,795	2,203	2,643		
31,8 x 31,8	1,003	1,233	1,530	2,016	2,488	2,948		
35 x 35	1,081	1,302	1,612	2,115	2,604	3,124		
38,1 x 38,1	1,208	1,450	1,813	2,380	2,975	3,424		
40 x 40	1,251	1,494	1,852	2,434	3,003	3,562		
45 x 45		1,687	2,090	2,756	3,405	4,040		
50 x 50		1,882	2,332	3,078	3,806	4,533	5,248	
50,8 x 50,8		2,065	2,468	3,286	4,108	4,929	5,751	
60 x 60			2,815	3,724	4,612	5,494	6,359	
70 x 70			3,303	4,379	5,443	6,494	7,532	
80 x 80			3,789	5,040	6,268	7,484		
100 x 100				6,400	7,969	9,525	11,069	12,600
120 x 120				7,660	9,544	11,415	13,274	15,120