

RUČNÍ A PNEUMATICKÉ KLAPKOVÉ VENTILY LKB – NEREZOVÉ
ROZMĚROVÁ TABULKA

Rozměry (mm) ventil LKB, LKB-2, LKB-F															
světlost ventilu	25 mm	38 mm	51 mm	63,5 mm	76,1 mm	101,6 mm	DN 25	DN 32	DN 40	DN 50	DN 65	DN 80	DN 100	DN 125	DN 150
A	42,0	42,0	61,0	61,0	79,5	106,0	42,0	42,0	42,0	61,0	61,0	79,5	106,0	106,0	98,0
B	15,5	16,7	16,6	17,5	16,6	16,0	14,7	15,9	16,7	16,6	17,5	16,0	16,0	18,0	18,0
C	49,0	49,0	58,5	69,5	73,5	93,0	48,0	49,0	54,0	63,0	75,0	79,0	93,0	115,0	122,0
OD	25,6	38,6	51,6	64,1	76,6	102,2	30,0	36,0	42,0	54,0	70,0	85,0	104,0	131,0	156,0
ID	22,5	35,5	48,5	60,5	72,0	97,6	26,0	32,0	38,0	50,0	66,0	81,0	100,0	125,0	150,0
t	1,55	1,55	1,55	1,8	2,3	2,3	2,0	2,0	2,0	2,0	2,0	2,0	2,0	3,0	3,0
E	32,5	32,5	42,0	52,0	57,0	77,0	33,3	33,3	37,7	46,6	57,3	63,0	77,0	96,7	104,0
F	78,0	78,0	99,0	117,0	132,0	169,0	79,0	79,0	86,5	105,7	125,0	143,0	169,0	199,0	215,0
G	8,0	8,0	8,0	8,0	10,0	10,0	8,0	8,0	8,0	8,0	10,0	10,0	12,0	14,0	15,0
H ₁	47,0	47,0	52,0	54,0	62,0	80,0	47,0	47,0	47,0	52,0	62,0	64,0	80,0	110,0	80,0
H ₂	83,0	83,0	92,0	92,0	114,0	132,0	83,0	83,0	83,0	92,0	114,0	116,0	132,0	136,0	152,0
J	82,0	82,0	92,0	102,0	107,0	127,0	74,0	74,0	78,0	88,0	98,0	104,0	118,0	150,0	161,0
K	120,0	120,0	120,0	120,0	162,0	162,0	120,0	120,0	120,0	120,0	162,0	162,0	162,0	223,0	338,0
L IDF/ISO	45,0	45,0	47,5	48,5	52,5	61,5									
M IDF/ISO	55,5	55,5	58,0	59,0	63,0	81,5									
L DS	42,0	43,5	46,0	51,0	55,0	64,0									
M DS	51,0	52,5	55,0	56,0	61,0	72,0									
L SMS	38,5	43,5	46,0	51,0	55,0	75,0									
M SMS	51,0	52,5	55,0	56,0	61,0	72,0									
L BS	45,7	45,7	48,2	49,2	53,2	67,0									
M BS	56,5	56,5	59,0	60,0	64,0	85,4									
L DIN	45,5	45,5	48,0	52,0	61,0	70,0	40,0	40,0	37,0	37,0	43,0	48,0	54,0	55,0	
M DIN	61,5	61,5	66,0	67,0	71,0	83,0	46,5	48,5	49,5	55,0	61,0	62,0	77,0	72,0	
L svorka	45,0	45,0	42,5	55,0	59,0	68,0									
N	26,5	26,5	30,5	40,5	43,5	53,0	27,3	27,3	31,7	35,1	45,8	49,5	53,0	72,7	85,0
P	42,0	42,0	46,0	46,0	58,0	58,0	42,0	42,0	42,0	46,0	58,0	58,0	58,0	62,0	78,0
váha LKB-F	1,6	1,3	2,1	2,9	5,0	7,9	1,6	1,6	1,7	2,6	4,7	5,8	7,9	11,7	12,3
váha LKB/LKB-2	1,2	1,0	1,5	2,1	3,0	4,7	1,2	1,1	1,3	1,8	3,0	3,5	5,1	7,5	9,0

Poznámka: Váhy (kg) jsou platné pro ventily s navařovacím připojením a ruční pákou.

Rozměry (mm) pneupohon LKLA a LKLA-T								
světlost ventilu	25–63,5 DN 25–50	76,1 DN 65–80	101,6 DN 100	101,6 DN 100	DN 125	DN 125	DN 150	DN 150
A ₁	244	242	242	363	246	363	246	363
A ₂	193	191	191	316	195	316	195	316
A ₃	244	244	244	337	244	337	244	337
A ₄	173	173	173	290	173	290	173	290
D	85	85	85	133	85	133	85	133
d	17	17	17	30	20	30	20	30
I	16,5	16,5	16,5	34	16,5	34	16,5	34
S	8	10	12	12	14	14	15	15
provedení	NC, NO, A/A	NC, NO, A/A	NC, NO, A/A	NC, NO, A/A	A/A	NC, NO, A/A	A/A	NC, NO, A/A

Připojení vzduchu: R 1/8 " (BSP), vnitřní závit.