

TRUBKY ANSI ROZMĚRŮ – SVAŘOVANÉ

NEREZOVÉ TRUBKY PODÉLNĚ SVAŘOVANÉ

ASTM A 312

ATESTY DLE EN 10204/3.1B

TOL. ASTM A 530

rozměr	A.D x W.D. (mm)	kg/m	17240/17249 (1.4301/1.4306)	17346/17349 (1.4401/1.4404)
3/8" 10S	17,15 x 1,65	0,640	•	•
3/8" 40S	17,15 x 2,31	0,858	•	•
1/2" 5S	21,34 x 1,65	0,820	•	•
1/2" 10S	21,34 x 2,11	1,014	•	•
1/2" 40S	21,34 x 2,77	1,285	•	•
3/4" 5S	26,67 x 1,65	1,035	•	•
3/4" 10S	26,67 x 2,11	1,299	•	•
3/4" 40S	26,67 x 2,87	1,713	•	•
1" 5S	33,40 x 1,65	1,330	•	•
1" 10S	33,40 x 2,77	2,125	•	•
1" 40S	33,40 x 3,38	2,541	•	•
1 1/4" 5S	42,16 x 1,65	1,690	•	•
1 1/4" 10S	42,16 x 2,77	2,735	•	•
1 1/4" 40S	42,16 x 3,56	3,444	•	•
1 1/2" 5S	48,26 x 1,65	1,950	•	•
1 1/2" 10S	48,26 x 2,77	3,158	•	•
1 1/2" 40S	48,26 x 3,68	4,112	•	•
2" 5S	60,33 x 1,65	2,450	•	•
2" 10S	60,33 x 2,77	3,990	•	•
2" 40S	60,33 x 3,91	5,521	•	•
2 1/2" 5S	73,03 x 2,11	3,770	•	•
2 1/2" 10S	73,03 x 3,05	5,342	•	•
2 1/2" 40S	73,03 x 5,16	8,810	•	•
3" 5S	88,90 x 2,11	4,585	•	•
3" 10S	88,90 x 3,05	6,557	•	•
3" 40S	88,90 x 5,49	11,466	•	•
3 1/2" 5S	101,60 x 2,11	5,290	•	•
3 1/2" 10S	101,60 x 3,05	7,526	•	•
4" 5S	114,30 x 2,11	5,927	•	•
4" 10S	114,30 x 3,05	8,496	•	•
4" 40S	114,30 x 6,02	16,322	•	•
5" 10S	141,30 x 3,40	11,740	•	•
6" 5S	168,30 x 2,77	11,480	•	•
6" 10S	168,30 x 3,40	14,040	•	•
6" 40S	168,30 x 7,11	28,720	•	•
8" 5S	219,10 x 2,77	15,000	•	•
8" 10S	219,10 x 3,76	20,270	•	•
8" 40S	219,10 x 8,18	43,410	•	•
10" 5S	273,00 x 3,40	23,090	•	•
10" 10S	273,00 x 4,19	28,340	•	•
12" 5S	323,90 x 3,96	31,880	•	•
12" 10S	323,90 x 4,57	36,720	•	•