

TRUBKY ANSI ROZMĚRŮ – ŽÁRUVZDORNÉ

BEZEŠVÉ ŽÁRUVZDORNÉ TRUBKY

ASTM / ASME A / SA 312

SEW 470

rozměr	A.D x W.D. (mm)	kg/m	17255 (1.4845)
1/4" 40S	13,72 x 2,24	0,634	●
3/8" 40S	17,15 x 2,31	0,845	●
1/2" 40S	21,34 x 2,77	1,268	●
1/2" 80S	21,34 x 3,73	1,620	●
3/4" 40S	26,67 x 2,87	1,684	●
3/4" 80S	26,67 x 3,91	2,195	●
1" 40S	33,40 x 3,38	2,502	●
1" 80S	33,40 x 4,55	3,237	●
1 1/4" 40S	42,16 x 3,56	3,389	●
1 1/2" 40S	48,26 x 3,68	4,046	●
1 1/2" 80S	48,26 x 5,08	5,409	●
2" 40S	60,33 x 3,91	5,440	●
2" 80S	60,33 x 5,54	7,485	●
2 1/2" 40S	73,03 x 5,16	8,636	●
2 1/2" 80S	73,03 x 7,01	11,413	●
3" 40S	88,90 x 5,49	11,292	●
3" 80S	88,90 x 7,62	15,273	●
4" 40S	114,30 x 6,02	16,075	●
5" 40S	141,30 x 6,55	21,765	●
6" 40S	168,30 x 7,11	28,262	●